SIEMENS

Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data: **1LE1603-1DB43-4AB4**

Motor type: **1CV3164B**

Client order no.: Item no.:
Order no.: Consignment no.:
Offer no.: Project:
Remarks:

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%] 4/4	3/4	2/4	Power factor at ... load 4/4	3/4	2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
400	Δ	50	15.00	- / -	28.50	1475	97.0	92.1	92.3	91.5	0.82	0.76	0.65	8.5	2.5	3.8	IE3
690	Y	50	15.00	- / -	16.70	1475	97.0	92.1	92.3	91.5	0.82	0.76	0.65	8.5	2.5	3.8	IE3
460	Δ	60	17.30	- / -	28.00	1775	93.0	93.6	93.7	92.9	0.83	0.78	0.68	8.5	2.5	3.7	IE3
460	Δ	60	15.00	- / -	25.00	1780	80.0	93.0	92.8	91.4	0.81	0.75	0.64	9.5	2.9	4.3	IE3
IM B3 / IM 1001		FS 160 L			127 kg	IP55	CC032A	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data

Sound pressure level 50Hz/60Hz (load)	65 dB(A)	69 dB(A)
Moment of inertia	0.085 kg m²	
Bearing DE | NDE	6309 Z C3	6309 Z C3
Relubrication interval/quantity	10 g | 10 g 8000 h	
Lubricants	Esso Unirex N3	
Regreasing device	Yes (standard)	
Grease nipple		
Type of bearing	Locating bearing NDE	
Condensate drainage holes	Yes (standard)	
External earthing terminal	No	
Vibration class	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	cast iron	
Data of anti condensation heating	-/-	
Coating	Special paint finish C3	
Color	RAL7030	
Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)	
Method of cooling	IC411 - self ventilated, surface cooled	

Environmental conditions

Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m

Terminal box

Terminal box position	top
Material of terminal box	cast iron
Type of terminal box	TB1 J01
Contact screw thread	M5
Max. cross-sectional area	16.0 mm²
Cable diameter from ... to ...	19.0 mm - 28.0 mm
Cable entry	2xM40x1,5-1xM16x1,5
Cable gland	3 plugs

Special design

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.